

TroytecDumps

👤 LOGIN / REGISTER | 🛒 MY CART (4) 🔍

WELCOME TO TROYTECDUMPS

The best real exam dumps & high-quality Troytec review files



TroytecDumps offering all the real Exam dumps and Troytec review files for exam certifications for most international largest companies. The pass rate for some company is reach to 100%. The average pass rate of Exam dumps is 99.39%.



Quality and Value

TroytecDumps Practice Exams are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development - no all dumps.



Tested and Approved

We are committed to the process of vendor and third party approvals. We believe professionals and executives alike deserve the confidence of quality coverage these authorizations provide.



Easy to Pass

If you prepare for the exams using our TroytecDumps testing engine, It is easy to succeed for all certifications in the first attempt. You don't have to deal with all dumps or any free torrent / rapidshare all stuff.



Try Before Buy

TroytecDumps offers free demo of each product. You can check out the interface, question quality and usability of our practice exams before you decide to buy.

<http://www.troytecdumps.com>

The best real exam dumps & high-quality Troytec review files

Exam : 920-221

Title : Nortel Converged Campus ERS
Installation and Configuration

Vendors : Nortel

Version : DEMO

NO.1 You are using the Nortel Network Command Line Interface (NNCLI) to modify a VLAN or a port. Which

NNCLI command mode are you using?

- A.Global Configuration Mode
- B.Interface Configuration Mode
- C.Privileged EXEC Mode
- D.Router Configuration Mode

Answer:B

NO.2 A customer would like to configure an IP address for an existing VLAN on an Ethernet Routing Switch

5510. You use the following Command Line Interface (CLI) command sequence: From the initial CLI

prompt, enter privilege mode, enter config mode, enter config-if mode for the VLAN interface.

Enter the

command, "ip address". What information do you enter next?

- A.Enter the appropriate IP address of the backup CPU.
- B.Enter the appropriate IP address and subnet mask in dotted decimal notation.
- C.Enter the appropriate IP address for the out-of-band management port.
- D.Enter the appropriate IP address for the in-band management port.

Answer:B

NO.3 You can use the User Interface (UI) button on the Ethernet Routing Switch 5500 to temporarily reset a

switch to the default IP address. Which two statements are true about the default IP address set via the UI

button? (Choose two.)

- A.The default IP address overrides the IP address currently in use by the switch stack.
- B.The default IP address overwrites the onfigured IP address settings that are set via console, Command Line Interface (CLI), or Web.
- C.The default IP address changes if there is a change in the state of the switch, such as if the switch joins or leaves a stack.
- D.The default IP address is saved in NVRAM across resets of the switch/stack.

Answer:A C

NO.4 If you do not know the IP address of an Ethernet Routing Switch 5510, how can you

upload code?

- A. Use Telnet.
- B. Use Console Access.
- C. Use the Web browser.
- D. Use the Java Device Manager.

Answer: B

NO.5 Which two statements are true about Power over Ethernet (PoE)? (Choose two.)

- A. PoE requires a significant increase in power capacity.
- B. PoE enables cooling systems and load-sharing power supplies.
- C. PoE provides increased power, resiliency, and redundancy at low cost.
- D. PoE is used to power IP telephones, Web cameras, and access points.

Answer: A D